

LIMITED WARHANTY NOTICE Every reasonable effort is made to apply BASF exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GURANTIEE, EVPRESS OR IMPLIED, INCLUDING WARRANTES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year form the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, sepecially patent rights. In particular, BASF disclaims all CON-DITIONS AND WARPANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLEID WARPANTIES OF FITNESS FOR A PARTICLLAR PURPOSE OR MERCHANTRABLITY, BASF SHALL, NOT BE RESPONSIBLE FOR CONSECUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments. It is the custome's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

Distributed by

Color Guide

Standard Colors for Sealants



BASF Construction Chemicals, LLC – Building Systems

889 Valley Park Drive Shakopee, MN 55379 www.BuildingSystems.BASF.com

Customer Service 800-433-9517 Technical Service 800-243-6739 Form No. 1017907 © 2008 BASF 1/08 Printed in U.S.A.



Standard Colors

	SL 2 [™] *			•	•		•	•		•		•		•	•	•	•	•	•	•		
	Polysulfide Sealant SL 1 [™]			•				•	•			•		•	•		•					
	NP 2 [™] *			•	•		•	•	•	•		•			•	•	•	•	•	•	•	•
	NP 1 [™]	•		•				•	•			•			•		•	•	•	•	•	•
	TX 1	•		٠		•		•			•		•		•		•	•	•		•	•
	Sonolastic [®] Sealant Systems PRODUCT NAME	Anodized Gray	Translucent	White	Cameo	Buff	Saltbox	Off White	Limestone	Riverbend	lvory	Tan	Natural Stone	Gray	Aluminum Gray	Precast Gray	Stone	Redwood Tan	Black	Hunter Green	Medium Bronze	Special Bronze
Hunter Green	Special Bronze	Special Bronze				Medium Bronze								Riverbend								
Black	lvory	lvory			ļ	Aluminum Gray									Redwood Tan							
Gray	Saltbox	Saltbox			1	Anodized Gray								Buff								
Precast Gray	Off White					Limes	tone								Tan							
Natural Stone	White	White				Cameo									Stone							

Custom colors and color formulas are available upon request to Customer Service. The color of actual products may vary; perform final color matching with actual material. Sonneborn® is not responsible for color matching when actual material is not used.

OmniPlus™

Ultra

0mniSeal[™] 50

Sonolac[®] **

150 with VLM Technology

•

•

.

•

•

.

.

.

•

•

.

•

. . .

•

.

•

. . . .

Also available in special colors