

# KING S MATERIAL INC.









# **KINGS-WALL**

TYPE "B" UNIT (for outside radius)



Weight: 58# ea Face size: 7" x 15 5%" 1.33 units/face sq ft of wall

10" CAP




Weight: 34# ea Face size: 4" x 15 5/8" 1 cap = 1.3 ln ft

### TYPE "B" RADIUS Bottom View Shown



Wall Height/Wall Length (measured at wall face)							
Total	Exposed	5'	10'	15'	20'	25'	30'
7"	6"	4	8	12	15	19	23
14"	12"	8	16	24	30	38	46
21"	18"	12	24	36	45	57	69
28"	24"	16	32	48	60	76	92
35"	30"	20	40	60	75	95	115
42"	36"	24	48	72	90	114	138
49"	42"	28	56	84	105	133	161

#### TYPICAL INSTALLATION SECTION



# K

#### **GENERAL NOTES**

- 1. Do not use pea gravel behind or under wall.
- 2. Compact base to prevent uneven settlement.
- 3. Lip may be broken off first course for ease of installation.
- 4. Compact backfill every course.
- 5. Level units both directions.
- 6. Do not exceed maximum height of 3' 7".

## COLORS



Due to inherent characteristics of concrete, color may vary slightly. No guarantee of color shade is made or implied.