

ENHANCE

Natural Stone Color

RESTORE

Natural Stone Beauty

PROTECT

Your Investment



Choose the Best Formula for Your Natural Stone Project



SRWI PRODUCTS Premium Stone Seal™ APPLICATION CHART	Surface Material					SRW Sealer Benefits				
	Granite/Quartz	Limestone	Marble/Travertine	Bluestone/Sandstone	Manufactured/Cultured Stone	Penetrating/Natural Look	Film-Forming/Enhancing	Reduce Salt/Frost Damage	UV Resistance	Commercial Grade
S-PS PENETRATING	X	X	X	X	X	X		X		
S-PSX PENETRATING X-TREME	X	X	X	X	X	X		X		X
S-HGX HIGH GLOSS X-TREME	X	X	X		X		X	X	X	X

S-PS Penetrating Premium Stone Seal



Benefits

- ▶ Invisible/natural-look finish
- ▶ Minimizes salt and freeze/thaw damage
- ▶ Seals and protects

Applications

- ▶ Granite/Quartz
- ▶ Limestone
- ▶ Marble/Travertine
- ▶ Bluestone/Sandstone

Not for use on structures under hydrostatic pressure



Instructions
bitly.com/S-PSsealer

S-PSX Penetrating X-treme Premium Stone Seal Commercial Grade



Benefits

- ▶ New 'Stain Preventer' technology
- ▶ Invisible/natural-look finish
- ▶ Recommended for high traffic walkways & commercial applications
- ▶ Protects stones from staining by water, oil, food and more



Applications

- ▶ Concrete/Clay Pavers
- ▶ Concrete Permeable Pavers

Not for use on structures under hydrostatic pressure



Instructions
bitly.com/S-PSXsealer

S-HGX High Gloss X-treme Premium Stone Seal Commercial Grade



NEW! 2016



Instructions
bitly.com/S-HGXsealer

Benefits

- ▶ High-gloss, wet-look finish
- ▶ Recommended for commercial and residential applications
- ▶ Highly durable, long-lasting protection in extreme conditions
- ▶ Enhances and protects

Applications

- ▶ Limestone
- ▶ Granite/Quartz
- ▶ Marble/Travertine
- ▶ Cultured Stone

Not for use on structures under hydrostatic pressure or permeable pavers



Premium Stone Clean SW Stone Wash Prepares NATURAL STONE for Sealing



NEW! 2016



Instructions
bitly.com/SWcleaner

Benefits

- ▶ Prepares natural stone surfaces prior to sealing
- ▶ Removes ground-in dirt, light grease and oil

Applications

- ▶ Granite/Quartz
- ▶ Limestone
- ▶ Marble/Travertine
- ▶ Bluestone/Sandstone

Not for use on sealed surfaces. Use after spot treatments.



DG Dual Guard Specialty Seal Commercial Grade



NEW! 2016



Instructions
bitly.com/DGsealer

Benefits

- ▶ 2 levels of protection in 1 application
- ▶ Long-lasting penetrating protection
- ▶ High-gloss, wet-look finish
- ▶ Acrylic/siloxane blend
- ▶ Commercial strength

Applications

- ▶ Concrete Pavers
- ▶ Most Natural Stone
- ▶ Wetcast
- ▶ Cultured Stone

Not for use on bluestone/sandstone or structures under hydrostatic pressure



FAQ

Get answers to our most commonly asked questions. Have a question not answered here? Call us toll-free at 800-752-9326 or e-mail customerservice@srwproducts.com

SRW
PRODUCTS

solid solutions to better hardscapes

How long should I wait to seal after installing polymeric sand?

Wait for sand to fully cure before sealing. Be sure the moisture has been released. We recommend waiting at least 28 days after polymeric sand installation.

What if there are stains on my natural stone?

Clean your stones with one or more of these SRW Specialty Clean™ products **before** you seal. Then, wait at least 24 hours before sealing to ensure surface and joints are completely dry.

OC Organic Stain Cleaner



Benefits

- ▶ Removes tar, gum, rubber and paint
- ▶ For use on granite/quartz, limestone, marble/travertine, bluestone/sandstone and fieldstone.

TR Tar Gum & Rubber Remover



Benefits

- ▶ Breaks down organic stains from leaves, pine needles, acorns, fruit, wine, etc.
- ▶ For use on granite/quartz, limestone, marble/travertine, bluestone/sandstone and fieldstone.

MC Mold, Moss & Mildew



Benefits

- ▶ Breaks down mold, moss, mildew, lichen and algae
- ▶ For use on granite/quartz, limestone, marble/travertine, bluestone/sandstone and fieldstone.

CD Cleaner & Degreaser



Benefits

- ▶ Removes grease, oil and dirt
- ▶ For use on granite/quartz, limestone, fieldstone and bluestone/sandstone

RE Rust Eliminator



Benefits

- ▶ Removes rust and hard water stains
- ▶ For use on granite/quartz and bluestone/sandstone

What do I use to clean up after sealing?



SRW XY Xylene is a fast-acting solvent that thins and dissolves acrylic sealer to aid in tool clean up and overspray.

What if I need to remove sealer?



SRW has a solution for every need. SS Sealer Stripper is a biodegradable, yet industrial-strength formula that removes sealing and curing compounds.

Is it necessary to use an SRW Slit Foam Roller?

Yes. A slit foam roller is the best choice for backrolling because it helps evenly distribute the sealer and prevent it from pooling.



Is it necessary to use a sprayer to apply?

While you can successfully apply SRW sealers using only a Slit Foam Roller, it is highly recommended that a sprayer is used to apply an even coat. A second person would then follow the sprayer with a slit foam roller to make sure the sealer is evenly distributed and prevent it from pooling.



Can I seal if rain is in the forecast?

SRW recommends a clear forecast for at least 24 hours before and after sealer application.